

DesignMax DM5SE surface-mounted loudspeaker

ARCHITECTS' & ENGINEERS' SPECIFICATIONS

OCTOBER 2019

The loudspeaker shall contain a two-way 5.25-inch woofer and 1-inch tweeter coaxially mounted within the Dispersion Alignment system.

The loudspeaker shall meet the following performance specifications: On-axis system frequency response shall be 65 Hz to 20 kHz (-10 dB) with the use of recommended active equalization. The loudspeaker sensitivity shall be 87 dB SPL in half-space environment with Bose EQ voicing with 1 W input at 1 meter. The long-term power handling rating shall be 60 W (AES test methodology using IEC system noise, 2-hour duration). Maximum continuous output shall be 105 dB SPL and the maximum peak output shall be 111 dB SPL, both in half-space environment with Bose EQ voicing. The nominal coverage pattern shall be 135° H x 135° V at 1-4 kHz.

The loudspeaker shall be constructed of an engineered plastics, UV fade resistant enclosure. The loudspeaker shall consist of PC-PBT plastic materials that are resilient to cooking oil exposure. The loudspeaker shall be in compliance with the following safety standards; UL1480A. The transducers shall be located behind a perforated aluminum grille with a powder-coated finish that is attached with a tamper-resistant design. The loudspeaker shall contain a u-bracket mounting system that attaches, adjusts and locks without the use of tools. The loudspeaker shall be suitable for use outdoors, with an ingress rating of IP55. The loudspeaker shall be available in black or white and shall be paintable. Input connectors shall be a Euroblock 6-pin connector with loop-through. The loudspeaker shall have a nominal rated impedance of 8 ohms and shall be wired in parallel with a line voltage matching (stepdown) transformer with a level selector appropriate for output taps of 3, 6, 12, 24, 50 Watts and Bypass (8 ohms). The loudspeaker input connections shall allow for direct connection to 70-volt, 100-volt or low-impedance amplifiers. Loudspeaker dimensions shall be 286 x 192 x 197 mm (11.25 x 7.56 x 7.75 in) and net weight shall be 4.75 kg (10.5 lbs).

Warranty shall be 5 years. The loudspeaker shall be the DesignMax DM5SE surface mounted loudspeaker.